MSP/MCD DECAL APPLICATION POLICY FOR SCHOOL BUSES

GLASS

Glass: General

All glass or plastic used in the vehicle must comply with applicable federal and state specifications. Any unmarked glass must have documentation for use in the specific position. *FMVSS 571.205*, *571.212*, *571.217*, *571.219*, *MCLA 257.1827*, *257.708a*, *257.709*, *NST-SBI 11.80*

YELLOW: Glazed surfaces containing any stickers not permitted by law.

YELLOW: Use of unauthorized tinting material which limits vision.

YELLOW: Any cracks, chips or discoloration over 1 - inch.

RED: Any glass not of approved type. NST-SBI 11.80

RED: Driver's side area window(s) chips, clouding, or cracks that obscure the driver's vision. *NST-SBI 11.80*

RED: Non-transparent material such as plywood is used to replace glass.

RED: Any sharp or exposed edges of glass that are not banded.

RED: Any missing window in the vehicle.

RED: Every school vehicle windshield shall be free of discoloration or other damage in that portion thereof extending upward from the height of the topmost portion of the steering wheel, but not including a one inch border at the top and a one inch border at each side of the windshield or each panel thereof, except that discoloration and damage as follows are allowed:

- Coloring or tinting applied during manufacture, for reduction of glare.
- Any crack not over 1-inch wide, if not intersected by any other crack.
- Any damaged area which can be covered by a disc 3/4 inch in diameter, if not closer than 3 inches to any other such damaged area. *NST-SBI 11.80*

Rubber Window Molding

RED: Any molding is damaged to the extent that the window is loose or breaking away from the vehicle.